



SUPERVISION

www.supervision.fr

CH10.6

perimeter display

CH10.6

perimeter display

■ **PIXEL PITCH** SMD LED • 10.6 mm

Module dimensions	1 536 W x 960 H x 120 D (mm)
Module weight	60,5 Kg
Module surface	1,47 m ²

TECHNICAL SPECIFICATIONS (*)	
VIEWING ANGLE	> 140°
RESOLUTION	6 480 pixels (video lines) / module - 8 760 pixels / m ²
BRIGHTNESS	6 000 Cd / m ² (NIT)
CEE FORM CONNECTION	electrical panel or 1 plug P17 1 plug 32 A up to 15 m ² / 1 plug 63 A up to 40 m ² / 1 plug 125 A if more 380 / 415 v 3P + N + G
VIDEO SIGNALS	DVI, HDMI; S-Video; VGA; RGB; Composite Video; SDI etc.
POWER SUPPLY	supply : 1,06 kVA / m ² (max.) - 0,53 kVA / m ² (average) power generator with automatic voltage regulator : 1,4 kVA / m ²
TILTING MECHANISM	yes
PROTECTIONS	yes
SOFTWARE	in option



© 2018 SUPERVISION

 (*) Subject to validation by Supervision for each project.

SUPERVISION

contact@supervision.fr | www.supervision.fr
Bât. DC3 - ZAC de la Prairie - 2 rue Vitruve
91140 Villebon-sur-Yvette FR
T + 33 (0) 1 69 79 91 20