



SUPERVISION

[www.supervision.fr](http://www.supervision.fr)

**LM11** mobile LED screen

# LM11

trailer mounted LED screen  
on rotating mast

■ **PIXEL** 8.33 mm Full Black SMD Led

Image 16/9	4 400 L x 2 400 l (mm)
Overall length on the road	7 000 mm
Overall weight when installed	9 T
Overall weight on the road	9 T
Overall height on the road	3 200 mm

## SPECIFICATIONS (\*)

VIEWING ANGLE	120°
RESOLUTION	528 x 288 pixels (video lines)
VIEWING DISTANCE	min. 8 m
BRIGHTNESS	≥ 4 500 Cd / m <sup>2</sup> (NIT)
DENSITY	14 400 Pixels / m <sup>2</sup>
CEE FORM CONNECTION	380 / 415 V 3P + N + G Electrical panel or 1 plug P17 - 32 A
POWER SUPPLY	supply : 10 kVA max. / 5,5 kVA average power generator with automatic voltage regulator (AVR) : 20 kVA
VIDEO SIGNALS	SDI HD / SD
TIME FOR INSTALLATION	30 min.

The screen is mounted on a hydraulic and rotating mast (360°), positioning the bottom of the image at 3,5 m from ground. With its integrated power generator and video control room, the LM11 is a self-contained unit. Thanks to its reduced space on ground, low weight and modern concept this screen can easily be installed at almost any location.

Integrated power generator  
Europower Model 18 kVA  
Tank volume : 60 l - Autonomy at full charge : 14h - Noise level at 7m : 68 dBA - Reference conditions : altitude 1000m / temperature -18°C to +40°C



(\*) Subject to validation by Supervision for each project

